SAFETY DATA SHEET



Product name Obeen UF 2 453852 SDS no. **L**ubricant Use of the For specific application advice see appropriate Technical Data Sheet or consult our company substance/preparation representative. Deutsche BP Aktiengesellschaft Industrial Lubricants & Services **Supplier** Erkelenzer Straße 20, D-41179 Mönchengladbach Germany Telefon: +49 (0)2161 909-30 Telefax: +49 (0)2161 909-392 **EMERGENCY TELEPHONE** Carechem: +44 (0) 208 762 8322 NUMBER E-mail address MSDSadvice@bp.com

1. Identification of the substance/preparation and company/undertaking

2. Hazards identification

This preparation is classified as dangerous according to Directive 1999/45/EC as amended and adapted.

Environmental hazards	Farmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Additional hazards	Note: High Pressure Applications Injections through the skin resulting from contact with the product at high pressure constitute a major
	medical emergency. See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.
See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.	

3. Composition/information on ingredients

Synthetic lubricant and additives Thickening agent

Chemical name	CAS no.	%	EINECS / ELINCS.	Classification	
Amine phosphate	80939-62-4	0.1 - 1	279-632-6	Xi; R36/38 N: R51/53	[1]
1H-imidazole-1-ethanol, 2-(8-heptadecenyl)-4,5-dihydro-	95-38-5	0.1 - 1	202-414-9	Xn; R22 C; R34 N; R50/53	[1]
N-Oleyl sarcosine	110-25-8	0.1 - 1	203-749-3	Xi; R41, R38 N; R50	[1]
See section 16 for the full text of the R-phrases declared a	above				
[1] Substance classified with a health or environmental hazard					
[2] Substance with a workplace exposure limit					
[3] PBT-substance					
[4] vPvB-substance					

Occupational exposure limits, if available, are listed in section 8.

4. First-aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms appear.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately.
Notes to physician	Freatment should in general be symptomatic and directed to relieving any effects. Note: High Pressure Applications Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.

Γ	Product name	Obeen UF 2	Product code 453852-DE03	Page: 1/4
	Version 2	Date of issue 6 February 2009	Format Switzerland Language	ENGLISH
			(Switzerland)	(ENGLISH)

5. Fire-fighting measures

Extinguishing media	
Suitable	In case of fire, use water spray (fog), foam, dry chemical or CO ₂ . This material is harmful to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Not suitable	Do not use water jet.
Hazardous decomposition products	Composition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Unusual fire/explosion hazards	This material is not explosive as defined by established regulatory criteria.
Special fire-fighting procedures	None identified.
Protection of fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

6. Accidental release measures

Personal precautions	✓ action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
Environmental precautions	
Large spill	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
Small spill	Stop leak if without risk. Move containers from spill area. Use a tool to scoop up solid or absorbed material and place into appropriate labelled waste container. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling	Avoid contact of spilt material and runoff with soil and surface waterways. Wash thoroughly after handling.
Storage	Keep container tightly closed. Keep container in a cool, well-ventilated area.
Water endangering class (CH)	1
Fire Class	F4s

8. Exposure controls/personal protection

Ingredient name **Occupational exposure limits** aluminum,(benzoato-o)hydroxy(octadecanoato-o)-SUVA (Switzerland). TWA: 2 mg/m³ 8 hour(s). Issued/Revised: 1/2001 Form: inhalable dust Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only. **Exposure controls Occupational exposure** Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits. controls **Hygiene measures** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. **Personal protective equipment Respiratory protection** None required. However, use of adequate ventilation is good industrial practice. Wear protective gloves if prolonged or repeated contact is likely. Hand protection Chemical-resistant gloves. Recommended: Nitrile gloves.

The correct choice of protective gloves. Recommended. Nutrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions. Safety glasses with side shields.

Eye protection Skin and body

Wear appropriate clothing to avoid prolonged skin contact.

Product name	Obeen UF 2	Product code 4538	52-DE03	Page: 2/4
Version 2	Date of issue 6 February 2009	Format Switzerland	Language	ENGLISH
		(Switzerland)		(ENGLISH)

9. Physical and chemical properties

General information	
<u>Appearance</u>	
Physical state	Ørease
Colour	Amber.
Odour	Mild
Important health, safety and envir	onmental information
Melting point / range	230°C (446°F)
Density	<1000 kg/m ³ (<1 g/cm ³) at 20°C
Solubility	insoluble in water.

10. Stability and reactivity

-	-
Stability	The product is stable.
Possibility of hazardous reactions	Moder normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	No specific data.
Materials to avoid	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	Combustion products may include the following: carbon oxides metal oxide/oxides
	Moder normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Chronic toxicity	
Chronic effects	No known significant effects or critical hazards.
Effects and symptoms	
Eyes	May cause mild eye irritation.
Skin	Folonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. Note: High Pressure Applications Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.
Inhalation	Vapours and aerosol can produce mucous membrane, nose, and throat irritation.
Ingestion	Ingestion may cause gastrointestinal irritation and diarrhoea.

12. Ecological information

Persistence/degradability	Inherently biodegradable
Mobility	Non-volatile. Grease insoluble in water.
Environmental hazards	Farmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. Disposal considerations

Disposal considerations / Waste information	The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.	
Unused product		
European waste catalogue (EWC)	₱2 01 12* spent waxes and fats	
(====)	However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.	
Packaging		
European waste catalogue (EWC)	5 01 10* packaging containing residues of or contaminated by dangerous substances	

14. Transport information

Not classified as hazardous for transport (ADR/RID, ADNR, IMDG, ICAO/IATA)

15. Regulatory information

Classification and labelling have been performed according to EU directives 1999/45/EC and 67/548/EEC as amended and adapted. Label requirements

Risk phrases	R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.		
Safety phrases	S61- Avoid release to the environment. Refer to special instructions/safety data sheet.		
Other regulations			
Europe inventory	All components are listed or exempted.		
United States inventory (TSCA 8b)	Ki components are listed or exempted.		
Australia inventory (AICS)	M components are listed or exempted.		
Canada inventory	🕅 least one component is not listed.		
China inventory (IECSC)	Al components are listed or exempted.		
Japan inventory (ENCS)	M components are listed or exempted.		
Korea inventory (KECI)	Not determined.		
Philippines inventory (PICCS)	Not determined.		
VOC content	0%		

16. Other information

Full text of R-phrases referred to in sections 2 and 3	 R22- Harmful if swallowed. R34- Causes burns. R41- Risk of serious damage to eyes. R38- Irritating to skin. R36/38- Irritating to eyes and skin. R50- Very toxic to aquatic organisms. R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
History	
Date of issue/ Date of revision	06/02/2009.
Date of previous issue	07/12/2006.
Prepared by	Product Stewardship Group
Notice to reader	
Indicates information that has ch	panged from previously issued version

Indicates information that has changed from previously issued version.

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

Product name	Obeen UF 2	Product code 45385	Product code 453852-DE03	
Version 2	Date of issue 6 February 2009	Format Switzerland	Language	ENGLISH
		(Switzerland)		(ENGLISH)